



EAE group of companies have over 2,500 employees worldwide and EAE products are used in more than 100 countries. EAE Group has over 30 patents, 300 brands and 100 industrial designs.



As EAE Technology, we provide innovative and value-added solutions for KNX applications. All our products are designed, developed, manufactured and tested in our headquarters in Istanbul, Turkey. EAE Technology products are in compliance with international open standards such as KNX, DALI, TCP/IP and WiFi.

EAE Technology is a member of KNX Association and an authorized KNX training center since 2012.

### **EAE Hotel GRMS Solutions**

all you need is EAE...

- Your guests feel at home with EAE hotel solutions,
- With EAE Hotel solution, your guests will feel home comfort,
- User-friendly minimalist design,
- Rich functional options.

Every detail in a hotel should match the guest's expectations. The main purpose of EAE Hotel solution is to create a solution that meets all needs with comfort, aesthetics and elegance. However, by creating an easily manageable organization with hotel management system integrations, ensuring the satisfaction of customer and hotel management together makes our hotel solutions more attractive.



#### **Comfort**

Your guests will get used to comfort with scenarios that make life easier (such as sleep, movie, comfort mode).



#### Design

Combines elegance and aesthetics with user-friendly design.



#### **Flexiblity**

Solutions can be developed according to your requests.





all you need is EAE...



Mona consist of user friendly elegant glass design.

It is suitable to be a part of your design, with various color options.



### **Switches**



You can reach all scenario types from a single point with user-friendly usage. Various switch alternatives from 1 button to 12 buttons.




### **DND MUR**



MONA DND MUR information display, where you can easily see whether your guests are in the room, consists of a 100% glass touch screen and includes room number, hotel logo, DND, Make Up and doorbell buttons.







### DND MUR

The Mona series DND MUR display, where you can easily see whether your guests are in the room, consists of a glass touch screen and includes room number, hotel logo, DND, Make Up indicators and doorbell buttons.



Touch operated



Glass surface





Frameless, minimalist design



Icon options









### bedside panel

Mona Serie offers all the solutions you need in hotel operations in the same concept. Mona continue to add value to your space with frameless design. A unique user experience with its touch design and minimalist icons. All the solutions you need are just a touch away.



Touch operated



Glass surface



Switch and Socket together



Frameless, minimalist design



Icon options




Away, comfort, night and protection modes




Independent programmable buttons



Various color option



All the socket options you need in one.







# welcome panel

When entering or leaving your room, desired scenarios can be realized with a single touch, and you can experience safety and comfort together thanks to the RF-ID card holder you use at the entrances.



Touch operated



Glass surface



Switch and Card Holder together



Frameless, minimalist design



Icon options



Away, comfort, night and protection modes



Independent programmable buttons











### thermostats

Mona thermostats continue to add value to your space with frameless design. Mona offers a unique user experience and intuitive operation with its touch design and minimalist icons.



Touch operated



Glass surface



Thermostat and switch together



Additional heating-cooling control



Frameless, minimalist design



Icon options



Fully automatic heating-cooling transition



Away, comfort, night and protection modes




Independent programmable buttons











### sockets

The Mona serie offers glass surface, minimalist design, wide collection up to 5 gang, wide range of colors, wide range core options.

#### MODULAR EUROPEAN SOCKETS



#### **EUROPEAN SOCKETS**



#### MODULAR BRITISH SOCKETS



#### **BRITISH SOCKETS**



#### MODULAR ITALIAN SOCKETS









2P+E - 13 A/250V ac - 15 A/127V ac

German Standard Power Socket



2P+E-16A-250V ac

SAT TV



0 db

SAT



τv Buttons

1M-1P-NO+NO-10 A With interlock

Push

Telephone

Data

USB power USB supply



Audio

Double RCA

Grounded Power Socket



2P+E - 13 A/250V ac - 15 A/127V ac

UPS Power Socket



2P+E - 13 A/250V ac - 15 A/127V ac

Child Proof Power Socket



2P+E - 13 A/250V ac - 15 A/127V ac

Telephone Socket



Double RJ11

Telephone Socket



RJ11

Data Socket



RJ45

SAT

Double USB power supply



British Standard Power Socket





SAT TV





SAT



ΤV

Push Buttons

Data Socket



RJ45 cat. 6 UTP







Switched




2P+E-13 A-250 V ac

Switched Power Socket



Switched **Power Socket** 





Switched

2P+E-13 A-250 V ac Twin

Switched **Power Socket** 





Switched

2P+E-13 A-250 V ac Twin - with USB

USB

Italian Standard Power Socket



2P+E-10A-250V ac 2P+E-16A-250V ac



SAT

ΤV



Push

Data Socket RJ45 cat. 6 UTP



Telephone

USB power

Socket supply Double USB power supply





Audio Socket



## product family

**Dnd Mur** 



Card Holder



Card Holder & Switch



Switch



Switch & Socket



Switch & Sockets



Thermostat



Thermostat & Switch




Thermostat & Switch & Socket



### variations

#### Switches



#### Thermostats



#### Card Holders









0 CEILING LIGHT

OFF















LIGHT



LIGHT















MUTE



DOWN























... other on request

#### Black Glass




White Glass



Hundreds of RAL surface colors...



## topology





# technical specifications



#### KNX Thermostat Side (up to 6 buttons)

- Temperature adjustment on display
- Integrated temperature sensor (°C/°F)
- Fan speed adjustment (1, 2, 3, Auto)
- Different operation modes (Comfort, Night, Away, Protection)
- Fully automatic function mode (Heat Cool transition)
- Control flexibility for all HVAC units including VRF-VRV and AC
- PI proportional, PI PWM, Hysteresis, Fan coil, Split unit controls



#### KNX Switch Side (up to 12 buttons)

Independent configuration for each button


- Switching
- Dimming
- Blind Control
- Value Transmitting
- Scene Control



#### KNX Card Holder Side (up to 6 buttons)


- Compatible with Mifare 13.56 MHz card
- Contactless reading for RFID Card information.
- Avoids mechanical wear and card deformation.
- Detection distance up to 50 mm

Dimensions (mm)	а	b	h
Single	90	12	110
Binary	161	12	110
Triple	232	12	110
Quadruple	303	12	110
Quintet	374	12	110



CE	In accordance with EMC guideline and low voltage regulation		
	Storage	-25° C + 55° C	
Temperature	Operating	-5° C + 45° C	
	Supply voltage	<<20 mA total	
Supply	Voltage Range	21-30V DC, Supply from EIB/KNX line	
Safety class	II	EN 61140	
Protection type	IP 20	EN 60529	

## product code legend



Note: Please contact our technical unit for details. (eaetechnology.salessupport@eaegroup.com)
The sockets should be at the beginning or end of the frame.
Module or core quantity must be specified at the end of the code.

#### Sample Order Code

FRAME EUROPEAN	MN-W-S05T02-FE1
FRAME MODULAR EUROPEAN	MN-B-S03-FME2X2M
FRAME MODULAR ITALIAN	MN-W-T02S03-FMI2
FRAME MODULAR BRITISH	MN-B-S03-FMB2
FRAME BRITISH	MN-W-CH03-FB1















#### **Thermostats**

Thermostat and switching control from one point with Rosa Thermostats.



#### **Switches**

Lighting, shutter/blind, scene call, speaker and DND/MUR control



#### Sockets

Various color options in UK, EU and universal standards.



### rosa metal thermostats

elegant and minimalist design

Rosa thermostats are designed for the needs of modern buildings. Rosa's intuitive design allows all ages to control their living space easily. New generation frameless design fits arqhitects' expectation and getting their compliments.



Touch operated



Brushed metal surface



Thermostat and switch together



Additional heating-cooling control



Frameless, minimalist design



Fully automatic heating-cooling transition



Icon options



Navigation LEDS



Feedback LEDS



Away, comfort, night and protection modes



Independent programmable buttons





2 Fold -Pearl White



2 Fold -Anthracite



2 Fold - Bronze



1 Fold - Natural



2 Fold - Gold







#### elegant and minimalist design

The Rosa glass switch and thermostat series, which has the same features as the metal ones in technical terms, can also be adapted to different concept designs with glass surface option. Rosa Glass can be colored according to the selected RAL code, adapts to the demands of the interior designers and fast changing trand.



Touch operated



4mm tempered glass surface



Thermostat and switch together



Additional heating-cooling control



Frameless, minimalist design



Fully automatic heating-cooling transition



Icon options



Navigation LEDs



Feedback LEDs



Comfort, night, protection and away modes



Independent, programmable buttons


















Rosa solid thermostats are designed for the needs of modern buildings. Rosa's intuitive design allows all ages to control their living space easily. New generation frameless design fits arqhitects' expectation and getting their compliments.



Touch operated



Glass surface



Thermostat and switch together



Additional heating-cooling control



Frameless, minimalist design



Fully automatic heating-cooling transition



Icon options



Navigation LEDs



Feedback LEDS




Away, comfort, night and protection modes



Independent programmable buttons









Rosa metal switches with 4 different color options add harmony and enrich to different designed homes, offices and hotel rooms. Rosa buttons can be configured independently and gives chance to users to control up tp 6 different objects.



Touch operated



Brushed metal surface



Frameless, minimalist design



Independent, programmable buttons



Icon options



Navigation LEDs



Feedback LEDs




Various color option



Rosa
2 Fold Metal Natural Switch







Rosa Crystal touch switches which has the same features as the metal ones adorn hotel rooms, homes and commercial buildings with its unlimited color options and 4mm tempered glass surface. Users are just defining the RAL code for coloring up the device.



Touch operated



4mm tempered glass surface



Frameless, minimalist design



Independent, programmable buttons



Icon options



Navigation LEDs



Feedback LEDs



Various color option


















Rosa Solid touch switches which has the same features as the metal ones adorn hotel rooms, homes and commercial buildings with its unlimited color options and 4mm tempered glass surface. Users are just defining the RAL code for coloring up the device.



Touch operated



4mm tempered glass surface



Frameless, minimalist design



Independent, programmable buttons



Icon options



Feedback LEDs



Navigation LEDs



Various color option







## Touch operated design...

Presicion detection for glass and metal surfaces.









## Brushed metal surfaces...

Rosa brushed metal thermostats contain 4 different color alternatives as natural (silver), gold, bronze and anthracite



## Independent programable buttons...

Each folds can be programmed as independent buttons.





### All in one...

Rosa offer switching and thermostat function controls from one point.

- · Lighting
- HVAC Control
- · Shading
- · DND/MUR
- · Scene Call







## Frameless design...

85 x 85mm frameless design



# Unlimited color options...

All RAL codes can be applied








## **High quality** raw materials...

7000 series aluminium is used for Rosa switch & thermostat.







## 4 mm tempered glass...

Conductive material coated glass surface is used for Rosa crystal & Rosa solid.





## **Additional Heating &** Cooling...

In built temperature sensor is used for Rosa serial.

Rosa thermostats have automatic heating/cooling change-over function. Additional heating/cooling units can be jointed to the system.





## Status LEDs...

Users can check the status of lighting, shutter/blinds and air conditioners in their living spaces with status of LEDs.








## **Navigation LEDs...**

It is easy and safe to reach your thermostat or switch in dark with the navigation LED on Rosa.



# Customizable icon options...

Rosa offers customized icon options for glass and brushed metal surface.





Rosa metal, crytal and solid framed sockets are designed for 4 different standards.

- √ Universal Standard
- √ Modular Standard
- √ British Standard
- √ European Standard



## **Universal** Standard

Single Socket - Natural




Single Socket - Bronze

Single Socket + Blind Cover - Natural


	а	h	<b>A</b>		
Single Single+ Sinary Triple	85 124 144 190	85 85 85 85	h	a	•

Binary Socket - Gold





CH100 Card Holder



### **Modular** Standard

Single Data - Natural



Binary USB + Data - Bronze



Triple Shaver Socket- Natural



	а	h
Single Binary Triple Quadruple Six	85 85 124 144 190	85 85 85 85



Quadruple Universal Socket + SAT/TV - Gold



Six Socket + SAT + Blind Cover - Anthracite



## **British** Standard

Single Socket - Bronze



Single Socket - Natural



Single Liht Switch - Bronze



Single 92 85 152 Binary



Binary Socket - Anthracite



Binary Socket+USB - Gold



## **European** Standard

Single Data - Bronze



Binary Socket + Phone - Gold

Triple Socket + TV - Natural



Quadruple Socket + Data + TV - Anthracite



	а	h	<b>^</b>
Single	85	85	h
Binary	156	85	-
Triple	227	85	а
Quadruple	298	85	
Quintet	369	85	

Quintet Socket + TV + Data - Bronze



Single Socket - Black Glass



Binary Socket+TV/SAT - White Glass



Triple Socket+SAT+Liht Switch - Black Glass



Quadruple	Socket+Liht	Switch+TV/SAT	- White Glass



a h
Single 85 85 h
Binary 156 85
Triple 227 85 a
Quadruple 298 85
Quintet 369 85

Quintet Socket+DATA+Liht Switch+Sat - Black Glass



## 



Light On / Off

Light Enhance / Dim


**Shutter-Blind** 

**DND** Do not disturb

MUR Makeup room



### **≪rosa** HERMOSTAT and SWITCH PRODUCT CODE LEGEND



Note: Icon grawing and front status options can not be applied at the same time on the same product.

Note\*: Selectable on both glass and metal surfaces.

Note\*: Selectable on glass surface only.




## **≪rosa**

### HERMOSTAT TECHNICAL SPECIFICATIONS




- Can be configured with ETS5.
- Serial thermostat with metal and glass touch-button
- Temperature control via digital LCD
- Internal temperature sensor (°C/°F)
- Adjustable fan speed (1, 2, 3, Automatic)
- Multiple operation modes (Comfort, Night, Outdoor, Indoor)
- Fully automated operation feature (hot-cold transition)
- Control of all HVAC units including VRF-VRV and air conditioning devices
- PI relative, PI on-off (PWM), On/Off, Fan coil, Split unit controls
- Easy installation to 60x60 mm standard switch junctions
- 2 dependent or 4 independent programmable buttons can be programmed for various functions.
  - Switching,
  - Dimming,
  - Shutter/Blind control,
  - Value and priority assignment,
  - Scene control,
  - Status notification LED

Protection type	IP 20	EN 60529	
Safety class	II	EN 61140	
Supply	Voltage Range	21-30V DC, Supply from EIB/KNX line	
	Supply voltage	<10 mA	
Temperature	Operating	-5° C + 45° C	
	Storage	-25° C + 55° C	
CE	In accordance with EMC guideline and low voltage regulation		
Case type to be used	60mm flush-mounted and surface-mounted safes between two mounting screws according to		
	European standards		




Dimensions (mm)	а	b	h
1 Fold Thermostat	85	11	85
2 Fold Thermostat	85	11	85

#### **Assembly Detail**



#### Important note!

The distance between the two thermostats should be at least **120 mm** from center to center.




## SWITCHES TECHNICAL SPECIFICATIONS




- Can be configured with ETS5.
- Serial switches with metal and glass touch-button
- Large collection option up to 4 Folds
- Product options with and without notification LED
- Optionally, icon branding is available.
- Different color options
- Easy installation to 60x60 mm standard switch junctions
- Channels are identical, each with the following functions;
  - Switching,
  - Dimming,
  - Shutter/Blind control,
  - Value and priority assignment,
  - Scene control,
  - Status notification LED

Protection type	IP 20	EN 60529
Safety class	II	EN 61140
Supply	Voltage Range	21-30V DC, Supply from EIB/KNX line
	Supply voltage	<10 mA
Temperature	Operating	-5° C + 45° C
	Storage	-25° C + 55° C
CE	In accordance with EMC guideling	ne and low voltage regulation
Case type to be used	60mm flush-mounted and surface	ce-mounted safes between two mounting screws according to
	European standards	




Dimensions (mm)	а	b	h
Single Switch	85	11	85
1 Fold Switch	85	11	85
2 Fold Switch	85	11	85
3 Fold Switch	85	11	85

#### **Assembly Detail**




#### Important note!

The distance between the two switches should be at least 120 mm from center to center.


















#### Thermostat

All devices in your home are under your control with Oria thermostats.






#### Switch

Experience life of comfort with Oria switches.



#### Socket

Socket group with eye catching design for perfect harmony.




# a simple touch, unlimited comfort thermostats

Expandable up to 4 folds, Oria thermostat provide a wide collection of possibilities for all spaces where both thermostats and programmable switches are needed at the same time.

Oria thermostats can perform all needed operations with a single touch. Programmable buttons on Oria thermostats can control comfort and energy saving needs such as lighting, shutter/blind, scene call,







Lifetime guarantee for surface quality














## a simple touch, unlimited comfort switches


The new generation of Oria switches adds a simple and elegant touch to the world of users while fulfilling unlimited needs with its design. With rich collection options expandable to 12 buttons in a single frame, enjoy one-point management of on-site lighting, heating-cooling, shutter-blind, speakers, scene call and panic buttons controls.





Lifetime guarantee for surface quality





# a simple touch, aesthetic integrity SOCKETS

As the supplementary item for the new generation of thermostat and switch series, Oria power outlets reflect the integrity of your space.



TV/SAT Mustang Gray



Socket Anthracite



Data Pearl White



TV/SAT Anthracite



UPS Mustang Gray



Liht Switch Pearl White



Data+Socket Pearl White



Socket+TV/SAT Anthracite




DATA+Socket+TV/SAT Pearl White




TV/SAT+Socket+Data+UPS Mustang Gray



## Orio THERMOSTAT and SWITCH ICON OPTIONS



# Oria THERMOSTAT and SWITCH PRODUCT CODE LEGEND



Note: Icon grawing and front status options can not be applied at the same time on the same product.








### ⊘oria HERMOSTAT TECHNICAL SPECIFICATIONS




- Can be configured with ETS5.
- Serial thermostat with plastic push-button
- Temperature control via digital LCD
- Internal temperature sensor (°C/°F)
- Adjustable fan speed (1, 2, 3, Automatic)
- Multiple operation modes (Comfort, Night, Outdoor, Indoor)
- Fully automated operation feature (hot-cold transition)
- Control of all HVAC units including VRF-VRV and air conditioning devices
- PI relative, PI on-off (PWM), On/Off, Fan coil, Split unit controls
- Easy installation to 60x60 mm standard switch junctions
- 2 dependent or 4 independent programmable buttons can be programmed for various functions.
  - Switching,
  - Dimming,
  - Shutter/Blind control,
  - Value and priority assignment,
  - Scene control,
  - Status notification LED

Protection type	IP 20	EN 60529
Safety class	II	EN 61140
Supply	Voltage Range	21-30V DC, Supply from EIB/KNX line
	Supply voltage	20 mA
	Power consumption	20 mA x 30V
Button operation life	100.000	
Temperature	Operating	-5° C + 45° C
	Storage	-25° C + 55° C
	Transport	-25° C + 70° C
CE	In accordance with EMC guideline and low voltage regulation	




Dimensions (mm)	а	b	h
2 Fold Thermostat	90	9	90
3 Fold Thermostat	90	9	111,5
4 Fold Thermostat	90	9	133

#### **Assembly Detail**



#### Important note!

The distance between the two thermostats should be at least 120 mm from center to center.




# Oria SWITCH TECHNICAL SPECIFICATIONS




- Can be configured with ETS5.
- Serial switches with plastic push-button
- Large collection option up to 4 Folds
- Product options with and without notification LED
- Optionally, icon branding is available.
- Different color options
- Easy installation to 60x60 mm standard switch junctions
- Channels are identical, each with the following functions;
  - Switching,
  - Dimming,
  - Shutter/Blind control,
  - Value and priority assignment,
  - Scene control,
  - Status notification LED

Protection type	IP 20	EN 60529	
Safety class	II	EN 61140	
Supply	Voltage Range	21-30V DC, Supply from EIB/KNX line	
	Supply voltage	15 mA	
	Power consumption	15 mA x 30V	
Button operation life	100.000		
Temperature	Operating	-5° C + 45° C	
	Storage	-25° C + 55° C	
	Transport	-25° C + 70° C	
CE	In accordance with EMC guideline and low voltage regulation		




Dimensions (mm)	а	b	h
Single Switch	90	9	90
1 Fold Switch	90	9	90
2 Fold Switch	90	9	90
3 Fold Switch	90	9	90
4 Fold Switch	90	9	90
5 Fold Switch	90	9	111,5
6 Fold Switch	90	9	133

#### **Assembly Detail**



#### Important note!

The distance between the two switches should be at least 120 mm from center to center.





## Touch the Future...


Using state-of-the-art technologies, Valesa Touch Panel enables you to manage your living environment-lighting, climate, cameras, security, intercom, blinds and more...




# **Comfort** at your fingertips...

With Valesa panel, of all ages in family can easily control lighting, heating-cooling, shutter-blind devices, activate burglar alarm, monitor cameras and use intercom to converse with incoming guests. You can easily call a taxi, valet or make SPA reservation easily by using integrated concierge services.

Helping to experience comfort in your home, Valesa panel technology is designed to meet all your needs from a single interface. In addition to adding elegance to chosen aesthetic of your spaces with a touch of design, Valesa panel will also become an essential part of your home.




IP based communications by reception staff





### TOPOLOGY



## STANDARD & CERTIFICATES

EAE Technology products are and will always be in compliance with international open standards such as KNX, DALI, TCP/IP and WiFi.




KNX is the worldwide standard for home and building control. KNX offers at the same time the reliability of a consolidated system, market leader for over twenty years. (470 KNX Members, 8000 Products, 470 KNX Training Centers, 83000 KNX Partners, 190 Countries)



DALI (Digital Addressable Lighting Interface) is a protocol for digital lighting control that enables the easy installation of robust, scalable and flexible lighting networks.





## SOME OF OUR REFERENCES













CENTRAL BALAT RESIDENCES
Bursa











**BONNEVILLE MIHRAPLI** *Turkey* 





FORTIS SINANLI





GAYDA ATAŞEHIR Istanbul





BALANCE GUNESLI





DIA BELLA

## SOME OF OUR REFERENCES













NATA VEGA AVM Ankara





TFF RIVA OTEL Istanbul









**EDIFICIO AMAYA**Spain













OLYMPUS RESIDENCE Izmir









**TURKCELL** DATA CENTER *Çorlu / Ankara* 







B/S/H/

**BSH** Cerkezkoy





TURKISH AIRLINES SIMULATION BUILDING Istanbul

















MILAHA LOGISTIC CITY

Qatar

















Istanbul























RCU FAMILY EAE KNX - ROOM CONTROL UNITS



PD100 / MD100 / CD100 EAE KNX - SENSOR



HLC103 EAE KNX - HOTEL LOGIC CONTROLLER



FCA100 EAE KNX - FANCOIL ACTUATOR



**UD105**EAE KNX - UNIVERSAL DIMMER



SD110 EAE KNX - 1-10V DIM ACTUATOR



DA100 / DA110 EAE KNX - DALI GATEWAY



SW108 / SW104 EAE KNX - RELAY MODULE



PSU320 / PSU640 EAE KNX - POWER SUPPLY 320mA/640mA



MIO1616 EAE KNX - MULTI INPUT OUTPUT



IPR100 / IPI100 EAE KNX - IP ROUTER



LC100 EAE KNX - LINE COUPLER



**UI108** EAE KNX - UNIVERSAL INTERFACE



CH100 EAE CARD HOLDER



HOTEL GRMS DEMO CASE




ROSA DEMO CASE



VALESA DEMO CASE







Ikitelli Organize Sanayi Bolgesi Eski Turgut Ozal Caddesi No:20 Başaksehir / Istanbul - TURKEY Tel. : +90 212 413 21 00 (pbx)

Fax: +90 212 549 37 90 www.eaetechnology.com





